

INDOOR EQUIPMENT CABINET

600mm (W) x 600mm (D) x 38U/43U, 19" Rack Mount

Specification

- 1 IP54 Standard
- 2 Polyester Structured Powder Coating, Light Grey, DIN 43.656 standard
- 3 Ventilated roof to facilitate brushed cable entry with cover plates.
- 4 Bottom plate with brushed cable entry with cover plates
- 5 Mounted on 4 x 70mm castors, two with brakes. **Min. load 200Kg.**
- 6 Lockable glass front door (Earthed with 6mm sq Cu cable to bottom plate)
- 7 Lockable rear door (Earthed with 6mm sq Cu cable to bottom plate)
- 8 Removable side panels (Earthed with 6mm sq Cu cable to bottom plate)
- 9 1U Front mountable (19") document holder to house DIN A4 documents
- 10 4 x Zinc plated Vertical profiles
- 11 2 x 220V AC Fans, air flow 160 cub. m/h
- 12 Vertical Brass earth bus bar with Faston 6.35mm connectors mounted rear RH side (Rear view)
- 13 **3 x 2U Modem trays**
- 14 1 x Battery shelf covered with acid resistant material; **battery weight 80kg.**
- 15 1 x Zinc plated Din rail, dimension 7mm x 35mm, 25mm hole pattern
- 16 220V AC Power strip with five outlets
- 17 10 x Plastic cable guides with fixing screws
- 18 50 x Cage nuts
- 19 **Cage nut insertion tool**
- 20 50 x Front fascias screws with Plastic washers
- 21 **Cable entry cover plates drilled with 3 x 16mm dia. holes for N-type panel mount connectors. Holes to be sealed with water tight plugs**

CABLE ENTRY COVER PLATE

